

CAD#120009B3

DRAWING NO.

12-0009

REV.

B

REQUIREMENTS	RATING	REQUIREMENTS	RATING
NOMINAL IMPEDANCE	50 Ohms	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G's)
FREQUENCY RANGE	DC TO 18.0 GHz		
TEMPERATURE COEFFICIENT	200 PPM	SHOCK	MIL-STD-202 METHOD 213 COND. I (100 G's)
OPERATING TEMPERATURE	-55 TO 125° C		
VSWR	1.20:1 MAX	TEMPERATURE SHOCK	MIL-STD-202 METHOD 107G COND. B (-65 TO +125° C)
AVERAGE POWER	3.0 WATT		
DC RESISTANCE	50 Ohms \pm 5%	BAROMETRIC PRESSURE	MIL-STD-202 METHOD 105 COND. C
		INTERFACE DIMENSIONS	MIL-C-39012C SMA SERIES
		TORQUE REQUIREMENT	MIL-D-39030/ SMA SERIES 7-10 IN/LBS (PER PAIR)
<p style="text-align: center;"><u>AVERAGE POWER DERATING</u></p>			

TITLE

TERMINATION, COAXIAL SMA



P.O. BOX 899
STUART, FL. 34995

DRAWN

PSC 5/25/95

SHEET

2 OF 2

DRAWING NO.

12-0009

REV.

B