

CAD#123001SFA3

DRAWING NO.

12-3001SF

REV.

A

REQUIREMENTS	RATING	REQUIREMENTS	RATING
NOMINAL IMPEDANCE (OHMS)	50	INTERFACE DIMENSIONS	MIL-STD-39012 /SMA Series
FREQUENCY RANGE (GHz)	DC - 18.0		
TEMPERATURE COEFFICIENT	LESS THAN 200 PPM	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G's)
OPERATING TEMPERATURE (°C)	-55 TO +125		
VSWR (MAXIMUM)	DC - 18.0 GHz: 1.20:1	SHOCK	MIL-STD-202 METHOD 213 COND. 1 (100 G's)
AVERAGE POWER (WATTS)	15		
DC RESISTANCE	50 OHMS ±2%	THERMAL SHOCK	MIL-STD-202 METHOD 107 COND. B (-65 TO +125)°C
		BAROMETRIC PRESSURE	MIL-STD-202 METHOD 105 COND. C
<p style="text-align: center;"><u>AVERAGE POWER DERATING</u></p>			

TITLE TERMINATION, SMA
JACK, 15 WATT



P.O. BOX 899
Stuart, FL. 34995

DRAWN GEC 04/07/97

SHEET 2 OF 2

DRAWING NO.

12-3001SF

REV.

A