



REQUIREMENTS	RATING	REQUIREMENTS	RATING
NOMINAL IMPEDANCE (Ohms)	50	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G'S)
FREQUENCY RANGE (GHz)	DC - 2.0		
TEMPERATURE COEFFICIENT	LESS THAN 200 PPM	SHOCK	MIL-STD-202 METHOD 213 COND. 1 (100 G'S)
OPERATING TEMPERATURE (°C)	-55 TO +150		
VSWR (MAXIMUM)	1.10:1	TEMPERATURE CYCLING	MIL-STD-202 METHOD 102 COND. C (-65 TO +125 °C)
		TERMINAL STRENGTH	MIL-STD-202 METHOD 211 COND. A
AVERAGE POWER (WATTS)	120	MOISTURE RESISTANCE	MIL-STD-202 METHOD 106 LESS STEP 7B
DC RESISTANCE	50 Ohms ±2%	SOLDERABILITY	MIL-STD-202 METHOD 208
		RESISTANCE TO SOLDER HEAT	MIL-STD-202 METHOD 210 COND. A
<p><u>AVERAGE POWER DERATING</u></p>			

TITLE

TERMINATION, FLANGE MOUNT,  
120 WATTP.O. BOX 899  
STUART, FL. 34995

DRAWN

GEC

SHEET

2 OF 2

DRAWING NO.

32-1160

REV.

N/C