

CAD#321162_3

DRAWING NO.

32-1162

REV.

N/C

REQUIREMENTS	RATING	REQUIREMENTS	RATING	
NOMINAL IMPEDANCE (Ohms)	50	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G'S)	
FREQUENCY RANGE (GHz)	DC - 2.0			
TEMPERATURE COEFFICIENT	LESS THAN 200 PPM	SHOCK	MIL-STD-202 METHOD 213 COND. 1 (100 G'S)	
OPERATING TEMPERATURE (°C)	-55 TO +150			
VSWR (MAXIMUM)	1.10:1	TEMPERATURE CYCLING	MIL-STD-202 METHOD 102 COND. C (-65 TO +125 °C)	
AVERAGE POWER (WATTS)	120	TERMINAL STRENGTH	MIL-STD-202 METHOD 211 COND. A	
DC RESISTANCE	50 Ohms ±2%	MOISTURE RESISTANCE	MIL-STD-202 METHOD 106 LESS STEP 7B	
<p><u>AVERAGE POWER DERATING</u></p>		SOLDERABILITY	MIL-STD-202 METHOD 208	
			RESISTANCE TO SOLDER HEAT	MIL-STD-202 METHOD 210 COND. A

TITLE
TERMINATION, FLANGE MOUNT,
120 WATT



P.O. BOX 899
STUART, FL. 34995

DRAWN

GEC

DRAWING NO.

32-1162

REV.

N/C

SHEET

2 OF 2