

REQUIREMENTS	RATING	REQUIREMENTS	RATING
NOMINAL IMPEDANCE (OHMS)	50	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G's)
FREQUENCY RANGE	DC- 1.5 GHz		
TEMPERATURE COEFFICIENT	LESS THAN 200 PPM	SHOCK	MIL-STD-202 METHOD 213 COND. 1 (100 G's)
OPERATING TEMPERATURE (degrees °C)	-55 TO +150		
VSWR (MAX)	1.20:1	TEMPERATURE CYCLING	MIL-STD-202 METHOD 102 COND. C (-65 TO +125° C)
AVERAGE POWER (WATTS)	60		
PEAK POWER (WATTS)	1.5 KW	TERMINAL STRENGTH	MIL-STD-202 METHOD 211 COND. A
DC RESISTANCE	50 OHMS ±2%		
		MOISTURE RESISTANCE	MIL-STD-202 METHOD 106 LESS STEP 7B
		SOLDERABILITY	MIL-STD-202 METHOD 208
		RESISTANCE TO SOLDER HEAT	MIL-STD-202 METHOD 210 COND. A
<p style="text-align: center;"><u>AVERAGE POWER DERATING</u></p>			

TITLE **TERMINATION, FLANGE
MOUNT 60 WATT**



P.O. BOX 899
STUART, FL. 34995

DRAWN **GEC 05/01/98**

DRAWING NO.

31-1168

REV.

N/C

SHEET 2 OF 2