

REQUIREMENTS	RATING	REQUIREMENTS	RATING
NOMINAL IMPEDANCE (Ohms)	50	VIBRATION	MIL-STD-202 METHOD 204 COND. D (20 G's)
FREQUENCY RANGE (GHz)	DC - 26.5		
TEMPERATURE COEFFICIENT	LESS THAN 200 PPM	SHOCK	MIL-STD-202 METHOD 213 COND. I (100 G's)
OPERATING TEMPERATURE (°C)	-55 TO +125		
VSWR (MAXIMUM)	DC-26.5: 1.20:1	THERMAL SHOCK	MIL-STD-202 METHOD 107 COND. B (-65 TO +125 ° C)
AVERAGE POWER (WATTS)	1		
DC RESISTANCE	50 OHMS ±5%	TERMINAL STRENGTH	2 LBS. MINIMUM PULL
		MOISTURE RESISTANCE	MIL-STD-202 METHOD 106 LESS STEP 7B
		SOLDERABILITY	MIL-STD-202 METHOD 208
		RESISTANCE TO SOLDER HEAT	MIL-STD-202 METHOD 210 COND. A
<p style="text-align: center;">AVERAGE POWER DERATING</p>			

TITLE TERMINATION, FLANGE
DC-26.5 GHz, 1 WATT



P.O. BOX 899
STUART, FL 34995

DRAWN GEC 02/11/97

DRAWING NO.

SHEET 2 OF 2

42-0054

REV.

N/C