EDD

NOTES:
UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE ± .010" [.254mm].

CAD#82-3019TC

DRAWING NO.:	REV.
82-3019TC	N/C





MATERIALS:
- SUBSTRATE: BERYLLIUM OXIDE
- COVER: ALUMINA
- TAB: BERYLLIUM COPPER PER ASTM B194
- RESISTIVE FILM: NICHROME

FINISH:
- SOLDERABLE GROUND PLANE: TIN/LEAD OVER NICKEL
- TAB: TIN/LEAD PER MIL-T-10727

ELECTRICAL: (TERMINATION)
- NOMINAL IMPEDANCE: 50 OHMS
- FREQUENCY RANGE: DC-1.0 GHz
- VSWR (MAX): 1.50:1
- AVERAGE POWER: 30 WATTS
- DC RESISTANCE: 50 ± 5% OHMS
- TEMPERATURE COEFFICIENT: ± 200 PPM MAX
- OPERATING TEMPERATURE: -55° TO +150° (°C)

REV.	DESCRIPTION	DRAWN	APVD.

EN# 04-F0164 | APVD | DATE

UNLESS OTHERWISE SPECIFIED
1. DO NOT SCALE DRAWING
2. DIMENSIONS ARE IN INCHES
3. DIMENSIONS ARE AFTER PLATING
4. CORNERS, EDGES AND FILLETS: R MAX
5. SURFACE ROUGHNESS: 63
6. REMOVE ALL BURRS

TOLERANCES
.X ±
.XX ±
.XXX ±
ANGLES X° ± X'

THE INFORMATION CONTAINED HEREIN IS: (A) CONSIDERED PROPRIETARY TO FLORIDA RF LABS INC.; (B) PROTECTED BY COPYRIGHT OWNED BY FLORIDA RF LABS INC.; (C) CONSIDERED A "WORK FOR HIRE" UNDER COPYRIGHT LAW; (D) PROTECTED BY TRADE SECRET LAWS WHICH MAKE ILLEGAL THE MISAPPROPRIATION OF THIS INFORMATION; AND (E) IS TO BE USED SOLELY FOR THE PURPOSE WHICH IT IS SUPPLIED. THIS INFORMATION SHALL NOT BE DISCLOSED IN WHOLE OR IN PART, TO ANY PARTY, FOR ANY REASON WITHOUT THE EXPRESS WRITTEN CONSENT OF A QUALIFIED EXECUTIVE OF FLORIDA RF LABS INC.

REFERENCE: CATALOG

MATERIAL: –

FINISH: –

FLORIDA RF Labs INC.
8851 OLD KANSAS AVE.
STUART, FL. 34997
772-286-9300

TITLE: TAB & COVER, TERMINATION, 30 WATT

SCALE	CAGE CODE ID NO.	SIZE	DRAWING NO.:	REV.
4/1	2Y194	A	82-3019TC	N/C

MFG: | CHKD.: | DRAWN: JAD 04/22/04 | SHEET OF